

Import JSON Code from API+jq

??????? ?????? ??????? ??????

В обратных кавычках Curl запрос с отфильтрованным fingerprint-ом ключа

```
sudo tee ~/key_convert << 'EOF'
#!/bin/bash
echo "{
  \"fingerprint\": `curl -X GET \
    -H 'Content-Type: application/json' \
    -H 'Authorization: Bearer <key>' \
    'https://api.digitalocean.com/v2/account/keys?page=1&per_page=999' \
    | jq '.ssh_keys[] | select(.name==\"REBRAIN.SSH.PUB.KEY\") | .fingerprint'`
}"
EOF
```

????????????? ???? ? ?????????????? terraform

Функция [lookup](#) извлекает значение указанного ключа из набора

```
data "external" "key_conv" {
  program = ["bash", "${path.root}/key_convert"]
}

resource "digitalocean_droplet" "ubuntu01" {
  ***

  ssh_keys = [
    "${lookup(data.external.key_conv.result, "fingerprint", "what?")}"
  ]
}
```

??????? jq-????????? ?????? ???????

Выгрузка значения **fingerprint** конкретного ключа по его **name**:

```
curl -X GET \  
  -H 'Content-Type: application/json' \  
  -H 'Authorization: Bearer <key>' \  
  'https://api.digitalocean.com/v2/account/keys?page=1&per_page=999' \  
  | jq '.ssh_keys[] | select(.name=="REBRAIN.SSH.PUB.KEY") | .fingerprint'
```

Выгрузка значений **name всех ключей:**

```
curl -X GET \  
  -H 'Content-Type: application/json' \  
  -H 'Authorization: Bearer <key>' \  
  'https://api.digitalocean.com/v2/account/keys?page=1&per_page=999' \  
  | jq '.ssh_keys[] | .name'
```

Revision #6

Created 2026-07-06 19:26:53 UTC by sa

Updated 2026-07-13 20:03:33 UTC by sa